

*University of Kragujevac*

*Faculty of Science*

**KRAGUJEVAC  
JOURNAL OF  
MATHEMATICS**

*Vol. 24*

*Kragujevac, 2002.*

UNIVERSITY OF KRAGUJEVAC  
FACULTY OF SCIENCE

KRAGUJEVAC  
JOURNAL OF  
MATHEMATICS

24

Kragujevac, 2002.

Volumes 1–21 of this journal appeared under the name “*Zbornik radova Prirodno-matematičkog fakulteta Kragujevac*” // “*Collection of Scientific Papers of the Faculty of Science Kragujevac*” and were published in the period 1980–1999. Beginning with volume 22 (for the year 2000) the journal split into two issues:

– “*Kragujevac Journal of Mathematics*”

and

– “*Kragujevac Journal of Science*” .

“*Kragujevac Journal of Mathematics*” publishes original scientific papers in mathematics and related fields. “*Kragujevac Journal of Science*” publishes original scientific papers in physics, chemistry, biology and related fields.

## Editorial Board

Dr. Dragić Banković, Editor-in-Chief

Dr. Ivan Gutman

Dr. Boško Jovanović

Dr. Jovan Mališić

Dr. Gradimir Milovanović

Dr. Miroslava Petrović-Torgašev

Dr. Slaviša Prešić

Dr. Božidar Radenković

Dr. Stojan Radenović

Dr. Miodrag Spalević, Managing Editor and Secretary

## C O N T E N T S

B. Popović	Abel, Niels Henrik (5. 8. 1802. - 6. 4. 1829.) Bolyai, Janos (5. 12. 1802. - 27. 1. 1860.) .....	5
A. Ossicini S. Ossicini M. M. Spalević	Remembering Alessandro Ossicini .....	7
V. R. Rosenfeld	Enumerating Kautz sequences .....	19
M. Lepović	A note on graphs with two main eigenvalues .....	43
V. O. Chiboka	The inner mappings of extra loops .....	55
I. Gutman	The star is the tree with greatest greatest Laplacian eigenvalue .....	61
M. Petrović I. Gutman	The path is the tree with smallest greatest Laplacian eigenvalue .....	67
D. Hajduković	Some problems about the limit of a real-valued function .....	71
Z. Starc	Power product inequalities for the gamma function .....	81
R. T. Trîmbiţaş	Univariate Shepard-Lagrange interpolation .....	85
K. Rauf C. O. Imoru	Some generalization of weighted norm inequalities for certain class of integral operators .....	95

M. Petrović- Torgašev	3-type curves in the Euclidean space $E^5$ ..... 107
M. Rajović D. Dimitrovski	The Clairaut and Lagrange areolar equation ..... 123
M. O. Ojo	Approximations of the distribution of the sum of random variables from the generalized logistic distribution ..... 135
M. Lazić	Formal grammar for a fragment of the Serbian language ..... 147
M. Lazić	A PROLOG program for analysis and synthesis of typical sentences taken from advertisements ..... 179
T. Obilade	A batch arrival queue providing a class of truncated geometric distribution for modeling distribution of animal populations ..... 193
B. R. Obrović <u>S. R. Savić</u>	About porosity parameters with the application of ge- neral similarity method to the case of a dissociated gas flow in the boundary layer ..... 207

*Kragujevac J. Math.* 24 (2002) 207–214.

## ABOUT POROSITY PARAMETERS WITH THE APPLICATION OF GENERAL SIMILARITY METHOD TO THE CASE OF A DISSOCIATED GAS FLOW IN THE BOUNDARY LAYER

Branko R. Obrović and Slobodan R. Savić

*Faculty of Mechanical Engineering, Sestre Janjić 6, 34000 Kragujevac, Yugoslavia*

*(Received March 6, 2002)*

**Abstract.** In this paper we have obtained the momentum equation for the ideally dissociated gas (air) flow in the boundary layer in the case of a porous contour of the body within fluid. We have also defined the set of porosity parameters  $\Lambda_k$  that is necessary for the application of generalized similarity method in order to solve different problems of compressible fluid flow.

### 1. STARTING EQUATIONS

As it is known [2], [4], generalized similarity method is based on the use of the momentum equation and on the application of infinite parameters sets that are accepted for new independent variables. Depending on the studied flow problem (incompressible fluid, MHD boundary layer, dissociated gas, ...), these parameters have different forms and they are related with different recurrent simple differential equations [2]. In this paper we have derived this momentum equation with the ideally dissociated

gas (air) flow in the boundary layer in the case when the contour of the body within fluid is **porous**. At the same time, a porosity parameter has been introduced and a set of porosity parameters of the ideally dissociated gas has been defined. A complete system of equations of the laminar planar and steady boundary layer of the ideally dissociated gas (air) [3] is:

$$\begin{aligned}
& \frac{\partial}{\partial x}(\rho u) + \frac{\partial}{\partial y}(\rho \nu) = 0, \\
& \rho u \frac{\partial u}{\partial x} + \rho \nu \frac{\partial u}{\partial y} = \rho_e u_e \frac{du_e}{dx} + \frac{\partial}{\partial y} \left( \mu \frac{\partial u}{\partial y} \right), \\
& \rho u \frac{\partial \alpha}{\partial x} + \rho \nu \frac{\partial \alpha}{\partial y} = \frac{\partial}{\partial y} \left( \rho D \frac{\partial \alpha}{\partial y} \right) + \dot{W}_A, \\
& \rho c_p \left( u \frac{\partial T}{\partial x} + \nu \frac{\partial T}{\partial y} \right) = -u \rho_e u_e \frac{du_e}{dx} + \frac{\partial}{\partial y} \left( \lambda \frac{\partial T}{\partial y} \right) + \mu \left( \frac{\partial u}{\partial y} \right)^2 \\
& \quad - (h_A - h_M) \dot{W}_A + \rho D (c_{pA} - c_{pM}) \frac{\partial \alpha}{\partial y} \frac{\partial T}{\partial y}, \\
& p = \rho T (1 + \alpha) \frac{k}{2m_A} = \rho T (1 + \alpha) R_M;
\end{aligned} \tag{1}$$

These equations represent respectively: the continuity equation, the dynamic equation, the equation of diffusion of the atomic component of the ideally dissociated gas, the energy equation and the state equation. The notation usual in the boundary layer theory has been used for the physical values in the system of equations (1):  $u(x, y)$  – longitudinal projection of the velocity in the boundary layer,  $\nu(x, y)$  – transversal projection of the velocity,  $\rho$  – density,  $p$  – pressure,  $\mu$  – dynamic viscosity coefficient,  $\alpha$  – mass concentration of the ideally dissociated gas atomic component,  $D$  – coefficient of the diffusion,  $\dot{W}_A$  – mass formation rate due to dissociation of gas molecules,  $c_p$  – specific heat of the gas (as a mixture),  $k$  – Boltzmann constant,  $\lambda$  – coefficient of thermal conductivity,  $T$  – absolute temperature,  $m$  – atomic and molecular mass of the ideally dissociated gas,  $R$  – gas constant and  $h$  – enthalpy. The subscripts represent:  $e$  – conditions at the outer edge of the boundary layer and  $A, M$  – atomic and molecular component of the ideally dissociated gas, respectively.

If, with  $\nu_w$ , we denote the given velocity of the dissociated gas flow through the solid porous wall of the body within fluid ( $\nu_w > 0$  at injection,  $\nu_w < 0$  at ejection) and transversal to it, then the corresponding boundary conditions are:

$$\begin{aligned} u = 0, \quad \underline{\nu = \nu_w(x)}, \quad T = T_w, \quad \alpha = \alpha_w \quad \text{for} \quad y = 0, \\ u \rightarrow u_e(x), \quad T \rightarrow T_e(x), \quad \alpha \rightarrow \alpha_e(x) \quad \text{for} \quad y \rightarrow \infty. \end{aligned} \quad (2)$$

Here and further on, the subscript w stands for the physical values at the wall of the body within fluid.

## 2. MOMENTUM EQUATION OF THE CONSIDERED PROBLEM

In order to obtain the momentum equation of the dissociated gas in the case of a porous contour of the body within fluid ( $\nu_w(x) \neq 0$ ), we start only from the continuity equation and the dynamic equation of the boundary layer of the system (1) of the considered problem.

If the continuity equation is multiplied with  $u_e(x)$ , where  $u_e(x)$  is the known velocity of the ideally dissociated gas at the outer edge of the boundary layer, then this equation comes down to:

$$\frac{\partial}{\partial x}(\rho u u_e) + \frac{\partial}{\partial y}(\rho \nu u_e) = \rho u \frac{du_e}{dx}.$$

Because of the continuity equation, the dynamic equation of the system (1) can be transformed into:

$$\frac{\partial}{\partial x}(\rho u^2) + \frac{\partial}{\partial y}(\rho u \nu) = \rho_e u_e \frac{du_e}{dx} + \frac{\partial}{\partial y} \left( \mu \frac{\partial u}{\partial y} \right).$$

Subtracting these equations we get:

$$\frac{\partial}{\partial x}(\rho u u_e - \rho u^2) + \frac{\partial}{\partial y}(\rho \nu u_e - \rho u \nu) = \frac{du_e}{dx}(\rho u - \rho_e u_e) - \frac{\partial}{\partial y} \left( \mu \frac{\partial u}{\partial y} \right).$$



Analogous to the way we derive the momentum equation of incompressible fluid, the previous equation can be integrated term by term with respect to the variable  $y$ , starting from the inner to the outer edge of the boundary layer, i.e., transversally to the layer. Taking the boundary conditions into consideration (2) and presuming the possibility of changing the order of differentiation and integration, we obtain:

$$\frac{d}{dx} \left[ \int_0^\infty \rho u (u_e - u) dy \right] - \underline{\rho_w \nu_w u_e} = \frac{du_e}{dx} \int_0^\infty (\rho u - \rho_e u_e) dy + \left( \mu \frac{\partial u}{\partial y} \right)_{y=0}. \quad (3)$$

This equation represents Kármán's integral relation for the considered case of the ideally dissociated gas flow.

In order for this momentum equation of the considered problem to be of the same form as the momentum equation of the corresponding problem of incompressible fluid flow, it is necessary to introduce new variables. So, analogous to other compressible fluid flow problems [3], instead of the physical coordinates  $x$  and  $y$ , we introduce a new longitudinal  $s(x)$  and a new transversal variable  $z(x, y)$  in the form of the following relations:

$$s(x) = \frac{1}{\rho_0 \mu_0} \int_0^x \rho_w \mu_w dx, \quad z(x, y) = \int_0^y \frac{\rho}{\rho_0} dy. \quad (4)$$

In the transformations (4),  $\rho_0$  and  $\mu_0$  represent an approximate known value of the density and the coefficient of dynamic viscosity, while  $\rho_w(x)$  and  $\mu_w(x)$  are their the given known values at the inner edge of the boundary layer.

By means of the newly introduced variables, the equation (3) is brought to:

$$\frac{d}{ds} \left( u_e^2 \Delta^{**} \right) + u_e \frac{du_e}{ds} \Delta^* = \frac{\rho_w \nu_w u_e}{\underline{\rho_0 ds/dx}} + \frac{\tau_w}{\rho_0 ds/dx}, \quad (5)$$

where the conditional displacement thickness  $\Delta^*$ , the conditional momentum loss thickness  $\Delta^{**}$ , tangential stress at the wall of the body within fluid  $\tau_w$ , and non-dimensional function of the friction  $\zeta$  are determined as:

$$\Delta^*(s) = \int_0^\infty \left( \frac{\rho_e}{\rho} - \frac{u}{u_e} \right) dz, \quad \Delta^{**}(s) = \int_0^\infty \frac{u}{u_e} \left( 1 - \frac{u}{u_e} \right) dz, \quad (6)$$

$$\tau_w = \left( \mu \frac{\partial u}{\partial y} \right)_{y=0} = \frac{\rho_w \mu_w}{\rho_0} \frac{u_e}{\Delta^{**}} \zeta, \quad \zeta(s) = \left[ \frac{\partial(u/u_e)}{\partial(z/\Delta^{**})} \right]_{z=0}.$$

After a little simpler transformations, the equation (5) can be brought to:

$$\frac{d}{ds} \left( \frac{\Delta^{**2}}{\nu_0} \right) + \frac{2}{u_e} \frac{u'_e \Delta^{**2}}{\nu_0} \left( 2 + \frac{\Delta^*}{\Delta^{**}} \right) = \frac{2}{u_e ds/dx} \left( \frac{\rho_w \mu_w}{\rho_0 \mu_0} \zeta + \frac{\rho_w \nu_w \Delta^{**}}{\rho_0 \nu_0} \right), \quad (7)$$

where “ ’ ” stands for the derivation with respect to the longitudinal variable  $s$ , while  $\nu_0 = \mu_0/\rho_0$ .

Introducing the common symbols and the parameter of the form  $f$ :

$$Z^{**} = \frac{\Delta^{**2}}{\nu_0}, \quad f = u'_e \Delta^{**2} \nu_0 = u'_e Z^{**} = f_1; \quad \frac{\Delta}{\Delta^{**}} = H, \quad (8)$$

the equation (7) reduces to it is final form

$$\frac{dZ^{**}}{ds} = \frac{F_{dp}}{u_e}. \quad (9)$$

It represents the momentum equation of the dissociated gas and it has the same form as the momentum equation of incompressible fluid. The characteristic function  $F_{dp}$  of the dissociated gas in the case of a porous contour, in the equation (9), is determined with the expression:

$$F_{dp} = 2[\zeta - (2 + H)f] + 2 \frac{\mu_0}{\mu_w} \frac{\nu_w \Delta^{**}}{\nu_0}. \quad (10)$$

It is noticed that the function  $F_{dp}$ , compared to the corresponding function in the case of a non-porous contour [3], contains an additional term. The given velocity  $\nu_w$  figures in this term, and it depends on the porosity of the contour of the body within fluid. Because of this a new parameter has been introduced in this paper – **the porosity parameter**. It is characterized by injection (or ejection) of the dissociated gas into the boundary layer, and it is determined with the expression:

$$\Lambda(s) = -\frac{\mu_0}{\mu_w} \frac{\nu_w \Delta^{**}}{\nu_0} = -\frac{V_w \Delta^{**}}{\nu_0} = \Lambda_1, \quad V_w = \frac{\mu_0}{\mu_w} \nu_w, \quad (11)$$

where  $V_w$  is the conditional velocity of injection.

In this way, the function  $F_{dp}$  comes down to:

$$F_{dp} = 2[\zeta - (2 + H)f] - 2\Lambda. \quad (12)$$

In this form it will be used in our further studies of the dissociated gas boundary layer.

### 3. INTRODUCTION OF A SET OF POROSITY PARAMETERS

The obtained momentum equation (9) can be written in yet another form. If the value  $Z^{**}$  is expressed by means of the parameter of the form (8)  $Z^{**} = f/u'_e$ , and if the differentiation with respect to  $s$  is performed, the momentum equation will be obtained in the following form:

$$\frac{df}{ds} = \frac{u'_e}{u_e} F_{dp} + \frac{u''_e}{u'_e} f \quad (13)$$

which is more convenient for application of the general similarity method.

Because of the relation (8) between the value  $Z^{**}$  and the conditional thickness  $\Delta^{**}$ , the porosity parameter (11) can be also written as:

$$\Lambda = -\frac{V_w}{\sqrt{\nu_0}} Z^{**1/2} = \Lambda_1 \quad (14)$$

where it follows that:

$$Z^{**} = \frac{\Lambda^2 \nu_0}{V_w^2}.$$

Based on this relation, from the momentum equation (9) we obtain:

$$\frac{d\Lambda}{ds} = \frac{d\Lambda_1}{ds} = \frac{u'_e}{u_e f_1} \left( \frac{1}{2} F_{dp} \Lambda_1 - u_e \frac{V'_w}{\sqrt{\nu_0}} Z^{**3/2} \right).$$

If the second addend in brackets is declared to be a new parameter  $\Lambda_2$

$$\Lambda_2 = -u_e \frac{V'_w}{\sqrt{\nu_0}} Z^{**3/2}, \quad (15)$$

the previous equation takes this form:

$$\frac{u_e}{u'_e} f_1 \frac{d\Lambda_1}{ds} = \frac{1}{2} F_{dp} \Lambda_1 + \Lambda_2 \equiv \chi_1. \quad (16)$$

Differentiating the parameter  $\Lambda_2$  with respect to the variable  $s$ , we will obtain:

$$\frac{u_e}{u'_e} f_1 \frac{d\Lambda_2}{ds} = \left( f_1 + \frac{3}{2} F_{dp} \right) \Lambda_2 + \Lambda_3 \equiv \chi_2, \quad (17)$$

where the value

$$\Lambda_3 = -u_e^2 \frac{V_w''}{\sqrt{\nu_0}} Z^{**5/2}, \quad (18)$$

is taken as the third porosity parameter.

If the parameter  $\Lambda_3$  is also differentiated with respect to the longitudinal variable  $s$ , we will get the equation:

$$\frac{u_e}{u'_e} f_1 \frac{d\Lambda_3}{ds} = \left( 2f_1 + \frac{5}{2} F_{dp} \right) \Lambda_3 + \Lambda_4 \equiv \chi_3, \quad (19)$$

where

$$\Lambda_4 = -u_e^3 \frac{V_w'''}{\sqrt{\nu_0}} Z^{**7/2}. \quad (20)$$

Continuing the shown procedure, with the next parameters and based on (14), (15), (18) and (20), it is easily concluded that the general porosity parameter  $\Lambda_k(s)$  is determined with the next expression

$$\Lambda_k = -u_e^{k-1} \left( \frac{V_w}{\sqrt{\nu_0}} \right)^{(k-1)} Z^{**k-1/2}, \quad (k = 1, 2, 3, \dots). \quad (21)$$

As the analysis indicates, any porosity parameter satisfies the recurrent equation

$$\frac{u_e}{u'_e} f_1 \frac{d\Lambda_k}{ds} = \{ (k-1)f_1 + [(2k-1)/2] F_{dp} \} \Lambda_k + \Lambda_{k+1} \equiv \chi_k. \quad (22)$$

whose right hand-side is marked with  $\chi_k$  ( $k = 1, 2, 3, \dots$ ) in order to make it shorter.

Finally, we must point out the necessity to introduce the set of porosity parameters (21) in order to apply the general similarity method by means of which the starting system of equations (1) of the ideally dissociated gas flow in the case of a porous contour of the body within fluid, is brought to a general form. This set of parameters of Loitsianskii's type, plays the role of new independent variables.

It is particularly important that the set of parameter  $\Lambda_k$ , obtained (defined) in this paper has the identical form as the corresponding set of parameters  $\lambda_k$  in the case of incompressible fluid flow [1], [2]. The corresponding expressions for the characteristic function  $F_{dp}$  and  $\chi_k$  are also identical. Of course, here the porosity parameters are expressed by means of the newly introduced variable  $s$  instead of the physical variable  $x$ , which is the case with incompressible fluid flow. Further more, in the conditions of incompressible fluid flow ( $\rho, \mu = \text{const.}$ ), the newly introduced variables (4) come down to  $s(x) \rightarrow x$ ;  $z(x, y) \rightarrow y$ , where the porosity parameter comes down to  $\Lambda_1 \rightarrow \lambda_1$  because in that case the conditional velocity of injection is  $V_w \rightarrow \nu_w$ .

These facts prove the correctness of defining sets of porosity parameters of the ideally dissociated gas in the form of the expressions (21). That is why in our further studies of dissociated gas flow in the case of a porous contour of the body within fluid, we shall use a set of porosity parameters in the form of the expression (21).

## References

- [1] Z. Boričić, D. Stakić, D. Nikodijević, *Free Convection with Arbitrary Temperature Distribution on a Vertical Porous Wall*, Bulletin for Applied Mathematics **644/89** (1989), 93–100.
- [2] L. G. Loitsianskii, *Mechanics of Fluids and Gases*, Nauka, Moscow, 1973., 1978.
- [3] B. Obrović, *Boundary Layer of Dissociated Gas (Monograph)*, Faculty of Mechanical Engineering, Kragujevac, 1994.
- [4] V. Saljnikov, Z. Boričić, D. Nikodijević, *Parametric Method in Unsteady MHD Boundary Layer Theory of Fluid with Variable Electroconductivity*, Facta Universitatis **2** No. 7/2 (1997), 331–340.

Izdavač: Prirodno-matematički fakultet u Kragujevcu,  
Radoja Domanovića 12, 34000 Kragujevac

Tiraž: 500 primeraka

Grafička oprema: Miodrag Spalević

Štampa: "Skver" Kragujevac

Redakcija zaključena oktobra 2002. godine

# INSTRUCTIONS TO AUTHORS

1. *Kragujevac Journal of Mathematics* is a periodical for mathematics. Requirements for acceptance of papers include originality, scientific significance and clarity of presentation.
2. Papers should be typed on good quality paper with double spacing and wide (3 cm) margins, using one side only, and submitted in duplicated (original and one copy) to: **Dr. Miodrag Spalević, Managing Editor of the Kragujevac Journal, Faculty of Science, P. O. Box 60, YU-34000 Kragujevac, Yugoslavia.**
3. The submitted contributions must be in English. Texts not written in English will not be considered for publication.
4. The papers should be written as usual in scientific journals. It is preferred that the references are ordered alphabetically. For details see the articles in the latest issues of this Journal.
5. All papers are refereed.
6. Upon the acceptance of a paper for publication, the author is requested to produce the final version of it in electronic form (and deliver it on a diskette of via e-mail) or to produce a camera-ready printout. For technical details consult the Managing Editor at [spale@knez.uis.kg.ac.yu](mailto:spale@knez.uis.kg.ac.yu).
7. In exceptional and justified cases papers may be submitted via e-mail.
8. The author will receive 20 reprints of his or her article free of charge. Additional reprints may be ordered.